

TERMÔMETROS ESPETOS

<u>Características / Modelo</u>							
	30.1040	9791.16.2.01	9795.02.3.00	6132	9226.16.0.00	T-DIV-0118.00	T-DIV-0122.00
<u>Escala de temperatura</u>	-40+250°C	-50+300°C	-50+300°C	-45+230°C	-50+300°C	-40+250°C	-50+150°C
<u>Função Máxima/Mínima</u>	✓	✓	✗	✗	✓	✗	✓
<u>Função HOLD</u>	✓	✓	✗	✓	✓	✗	✗
<u>Resolução</u>	0,1°C	1°C	0,1°C	0,1°C	0,1°C	0,1°C	0,1°C
<u>Precisão</u>	±0,5°C até 100°C	±1°C	±1°C	±1°C	±1°C	±0,5°C até 150°C	±1°C
<u>Tamanho da Haste</u>	105 mm	145 mm	145 mm	127 mm	140 mm	70 mm	120 mm
<u>Diâmetro da Haste</u>	2 a 4mm	4 mm	4 mm	2 a 4mm	4 mm	3,5 mm	8 mm
<u>A prova d'água</u>	✓	✓	✗	✗	✓	✓	✗
<u>Alarme</u>	✗	✓	✗	✗	✓	✗	✗
<u>Bateria</u>	1 pilha Lr44 x 1,5V	1 pilha Lr44 x 1,5V	1 pilha Lr44 x 1,5V	1 pilha Lr44 x 1,5V	2 pilhas AAA	1 pilha CR2032	1 pilha Lr44 x 1,5V
<u>Desligamento Automático</u>	10 Minutos	10 Minutos	45 Minutos	45 Minutos	60 Minutos	10 Minutos	60 Minutos
<u>Visualização Carga Baixa</u>	✗	✗	✗	✗	✓	✗	✗
<u>Peso</u>	50g	38g	38g	22g	181g	41g	78g
<u>OBSERVAÇÕES</u>		Função de Calibração no ponto 0°C			Cabo 90cm	Haste dobrável	Com ponta tipo saca-rolhas